

Masterbusn


ON SITE INCINERATION




The **MB450** is a top loading incinerator with a full width counter balanced lid which gives great access to the main chamber for loading of carcasses and easy ash removal.



This machine has found favour within the pig industry and small abattoirs along with larger poultry units.



The design of this model ensures extra air is drawn into the main chamber aiding primary combustion to ensure the efficient disposal of carcasses at minimum cost



Model No:
MB450

FEATURES

- DEFRA & DARD Type Approved
- 5mm Steel Construction
- 25mm High Density Insulation
- 75mm High Quality Refractory Lining
- Designed for Outdoor Use
- IP68 Rated
- Factory Wired
- Factory Installed Pipework
- Factory Test Fired
- 10 M Pipe For On Site Install
- 2 Stage Burners
- Individual Chamber Temperature Control
- Pre Incineration Warm Up Cycle
- Post Incineration Cool Down Cycle
- Variable Time Control
- 24hr Burner Exchange Service

Model No.

**MB
450**

Fuel Type
Cubic Capacity (Mtr)
Door Aperture (mm)

Oil
0.74
550 x 1800

EXTERNAL DIMENSIONS

Length (mm) 3110
Width (mm) 1500
Height incl. Flue (mm) 3300

INTERNAL DIMENSIONS

Length (mm) 2100
Width (mm) 550
Height (mm) 640

FUEL CONSUMPTION (GUIDE ONLY)

Gallons / hour 1.4

MINIMUM OPERATING TEMPERATURE

Degrees Centigrade 950

RESIDENCY TIME IN AFTERBURNER CHAMBER

Seconds 2

Temperature Monitoring

YES

INCINERATE UK LIMITED

Moss Side Farm
New Lane
Crossens
SOUTHPORT
PR9 8LN

01704 224756