

INCINER8

Waste Incineration Model A1000 / A1600

Animal & Waste Incinerators

We can now offer our range of incinerators exclusively throughout Europe and the rest of the world through our dealer network. Our range of units are fully CE certified, ensuring that we meet the highest standards in safety and construction. We also have a large range of DEFRA approved units which meet the ABPR regulations for incineration of animal by-products.



Model A1000(A)

Large Capacity Units Models A1000 and A1600

Our latest range of units lend themselves in particular to large animal carcasses such as pigs or calves. One of the unique features of this range is the full width counterbalance loading door allowing easy access to the main chamber for loading and removing ash.

The design of this model ensures extra air is drawn into the main chamber aiding primary combustion to ensure the efficient disposal of carcasses at minimum cost.

Ease of Use

Auto ignition. No pilots to light. Set the timer and walk away.
Built-in skid facilitates placement

Fuel Efficiency

Rapid incineration means low fuel consumption.
Higher burn rate than smaller models.
Thick refractory lining in main chamber retains heat, increasing efficiency.

Quality Built to Last

Heat resistant 5mm steel.
Stainless steel stack.



Model A1600(A)

KEY FEATURES

- Low running and maintenance costs
- Fully Automatic and simple to operate control panel
- Afterburner Preheat
- Incineration Temperatures in Excess of 1300 degrees C
- 5mm Steel Casing and Fully insulated
- Dense Refractory Concrete Lining Rated to 1600 degrees C
- Solid Hearth to Allow Maximum Burnout
- Large Top Opening Lid For Easy Loading
- Wide Door For Ash Removal
- Stainless Steel Flue as standard
- After Burner Fitted as standard
- 12 Month or 400 / 1000 hours Warranty.
- Optional Stainless Steel Casing
- CE Marking
- EU ABPR / DEFRA Approved
- Heat Recovery System option



Technical Specifications	Model A1000	Model A1600
Fuel	Oil	Oil
Capacity (Cubic Mtr)	0.68	1.18
Ave Capacity	450kg	750kg
Fuel Consumption (ltrs / hr)	7	6
External Dimensions		
Length (mm)	3110	3110
Width (mm)	1500	1800
Height Incl. Flue (mm)	4250	3300
Door Opening (mm)	550 x 1800	770 x 2000
Internal Dimensions		
Length (mm)	1800	2100
Width (mm)	550	700
Height Incl. Flue (mm)	640	800
Operation		
Min. Operating Temperature	950	950
Max. Operating Temperature	1320	1320
Residency Time in Second Chamber	2 secs.	2 secs.
Temperature Monitoring	YES	YES

Dealer Stamp

INCINER8

Shakespeare Hse. 37-39 Shakespeare Street, Southport PR8 5AB, England
 Tel +44 (0) 1704 548508
 Fax +44 (0) 1704542461
 Email : info@inciner8.com
 Web : www.inciner8.com