

INCINER8

Waste Incineration Model A1600

Animal & Waste Incinerators

We can now offer our range of incinerators exclusively throughout Europe and the rest of the world through our dealer network. Our range of units are fully CE certified, ensuring that we meet the highest standards in safety and construction.



Large Capacity Unit Model A1600

Our latest range of units lend themselves in particular to large animal carcasses such as pigs or calves. One of the unique features of this range is the full width counterbalance loading door allowing easy access to the main chamber for loading and removing ash.

The design of this model ensures extra air is drawn into the main chamber aiding primary combustion to ensure the efficient disposal of carcasses at minimum cost.

Ease of Use

Auto ignition. No pilots to light. Set the timer and walk away.

Built-in skid facilitates placement

Fuel Efficiency

Rapid incineration means low fuel consumption.

Available in higher burn rate than standard 50kgs per hour. Up to 150kgs per hour.

Thick refractory lining rated to 1600 deg C in main chamber retains heat, increasing efficiency.

Quality Built to Last



Model A1600 Internal

KEY FEATURES

- Low running and maintenance costs
- Fully Automatic and simple to operate control panel
- Afterburner Preheat
- Incineration Temperatures in Excess of 1300 degrees C
- 5mm Steel Casing and Fully insulated
- Dense Refractory Concrete Lining Rated to 1600 degrees C
- Solid Hearth to Allow Maximum Burnout
- Large Top Opening Lid For Easy Loading
- Wide Door For Ash Removal
- Stainless Steel Flue as standard
- After Burner Fitted as standard
- 12 Month or 1000 hours Warranty.
- CE Marking
- Heat Recovery System option



Technical Specifications

Model A1600

Fuel	Oil
Capacity (Cubic Mtr)	1.18
Ave Capacity	750 kg
Fuel Consumption (ltrs / hr)	10

External Dimensions

Length (mm)	3110
Width (mm)	1800
Height Incl. Flue (mm)	3300
Door Opening (mm)	770 x 2000

Internal Dimensions

Length (mm)	2200
Width (mm)	800
Height	800

Operation

Min. Operating Temperature	950
Max. Operating Temperature	1320
Residency Time in Second Chamber	2 secs.
Temperature Monitoring	YES

Dealer Stamp

INCINER8

INCINER8 House. Balmoral Drive,
Southport PR9 8PZ, England
Tel +44 (0) 1704 506506
Fax +44 (0) 1704506666
Email : info@inciner8.com
Web : www.inciner8.com