

INCINER8

Waste Incineration Model A200(M)

Animal & Waste Incinerators

We can now offer our range of incinerators exclusively throughout Europe and the rest of the world through our dealer network. Our range of units are fully CE certified, ensuring that we meet the highest standards in safety and construction.

Inciner8 pride ourselves on our high level of customer service and support. We have local dealerships in over 35 countries and also provide qualified telephone support when needed.



Model A200(M)

The Model A200(M) is ideally suited to small scale farms and benefits from an additional large secondary chamber to achieve ABPR standards for Category II animal waste. This extra post combustion chamber is highly durable and made from steel and high temperature refractory cement lining.

The unique design of the primary chamber ensures even incineration of waste material and also provides a secondary burn characteristic because the smoke and emissions are forced through the primary burner flame before exiting into the stack. The A200(M) achieves a 2 second gas retention time at over 850 deg C.

This unit has a chamber capacity of .18 cubic metres and can hold up to 100 kg with a burn rate of up to 40 kg per hour.

Model A200(M)

This proven design is in use in many different applications throughout the world.

The units have been designed to be extremely simple to install as they arrive on site 95% completed.

We provide a full warranty and technical back-up service either through our local dealerships or directly through our telephone support line.

All of our range of units are ideal for export because of their simplicity of operation and durability. We only use CE certified (Low Nox) burners for all of our incinerator range.



Model A200(M) Internal

KEY FEATURES

- Low running and maintenance costs
- Automatic and simple to operate control panel
- Afterburner Preheat
- Incineration Temperatures in Excess of 1000 degrees C
- 5mm Steel Casing and Fully insulated
- Dense Refractory Concrete Lining Rated to 1600 degrees C
- Solid Hearth to Allow Maximum Burnout
- Large Top Opening Lid For Easy Loading
- Stainless Steel Flue as standard
- 12 Month or 1000 hours Warranty.
- CE Marking
- Heat Recovery System option
- Easy on site installation



High Temperature Primary Chamber

Technical Specifications	Model A200(M)
Fuel	Oil or Gas
Capacity (Cubic Mtr)	0.18
Fuel Consumption (ltrs / hr)	5
External Dimensions	
Length (mm)	1070
Width (mm)	660
Height Incl. Flue (mm)	4000
Door Opening (mm)	460 x 510
Internal Dimensions	
Length (mm)	800
Width (mm)	580
Height Primary Chamber (mm)	560
Operation	
Min. Operating Temperature	950
Max. Operating Temperature	1320
Residency Time in Second Chamber	2 secs
Temperature Monitoring	YES

Dealer Stamp

INCINER8 UK

INCINER8 House. Balmoral Drive,
Southport PR9 8PZ, England
Tel +44 (0)1704 506677
Fax +44 (0)1704506666
Email : info@inciner8uk.co.uk
Web : www.inciner8uk.co.uk