

TECHNICAL SPECIFICATIONS

Technical Spec.	A200	A400	A600	A850	A200(A)	A400(A)	A600(A)	A850(A)	A200(Sec)	A400(Sec)
Capacity (Cubic Mtr)	0.18	0.36	0.54	0.75	0.18	0.36	0.54	0.75	0.18	0.36
Ave Capacity kgs	100	200	300	400	100	200	300	400	100	200
Shipping weight Kgs	630	920	1350	1850	880	1170	1600	2100	850	1090
External Dimensions										
Length (mm)	1070	1220	1520	1520	1070	1220	1520	1520	1070	1220
Width (mm)	660	910	910	1130	660	910	910	1130	660	910
Height Incl. Flue (mm)	2600	3300	4400	4400	3800	4100	5200	5200	3800	3900
Door Opening (cm)	46 x 51	56 x 74	66 x 76	53 x 69	46 x 51	56 x 74	66 x 76	53 x 69	46 x 51	56 x 74
Fuel Consumption (NB these consumption figures take into account the use of a temperature controller / thermostat being fitted)										
LPG Gas Ltr / hr	6	7	9	10	6	7	9	10	7	8
Diesel Oil Ltr / hr	5	6	8	9	5	6	8	9	6	7
Natural Gas M3	4.1	4.8	6.2	6.8	4.1	4.8	6.2	6.8	4.8	5.5
Operation										
Min. Operating Temp.	900	900	900	900	900	900	900	900	900	900
Max. Operating Temp.	1350	1350	1350	1350	1350	1350	1350	1350	1350	1350
Secondary chamber	No	No	No	No	YES	YES	YES	YES	YES	YES
Residency Time	N/A	N/A	N/A	N/A	2 secs	2 secs	2 secs	2 secs	.5 sec	.5 sec
Temp Monitoring	Optional	Optional	Optional	Optional	YES	YES	YES	YES	Extra	Extra
Thermostat Control	Optional	Optional	Optional	Optional	YES	YES	YES	YES	Extra	Extra
Constant Run fan	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
Burn Rate kgs / hr	35	45	45	48	35	45	45	48	35	45

Technical Spec.	A600(Sec)	A850 (Sec)	B60	A1600	A1600(HF)	A2600	A2600(HF)	P16	P25	P25 M1
Capacity (Cubic Mtr)	0.54	0.75	0.13	1.18	1.18	1.92	1.92	0.47	0.65	0.65
Ave Capacity kgs	300	400	60	750	750	1200	1200	200	350	350
Shipping weight Kgs	1520	2050	600	3500	3500	5500	5500	1100	1800	2100
External Dimensions										
Length (mm)	1520	1520	750	3110	3110	3110	3110	2000	2300	2600
Width (mm)	910	1130	750	1800	1800	2150	2150	1220	1220	1500
Height Incl. Flue (mm)	5000	5000	2000	3300	3300	3300	3300	6120	7700	7700
Door Opening (mm)	66 x 76	53 x 69	55 x 35	77 x 200	77 x 200	100 x 200	100 x 200	61 x 71	61 x 71	61 x 71
Fuel Consumption (NB these consumption figures take into account the use of a temperature controller / thermostat being fitted)										
LPG Gas Ltr / hr	10	12	4	10	12	10	12	8	12	13
Diesel Oil Ltr / hr	9	11	3	9	10	9	11	7	11	12
Natural Gas M3	6.8	8.2	2.7	6.8	8.2	6.8	8.2	4.8	8.2	8.9
Operation										
Min. Operating Temp.	900	900	600	900	900	900	900	900	900	900
Max. Operating Temp.	1350	1350	1350	1350	1350	1350	1350	1350	1350	1350
Secondary chamber	YES	YES	YES	YES	YES	YES	YES	YES	YES	Yes
Residency Time	.5 sec	.5 sec	1 secs	2 secs	2 secs	2 secs	2 secs	.5 sec	.5 sec	1 sec
Temp Monitoring	Optional	Optional	Optional	YES	YES	YES	YES	YES	YES	YES
Thermostat Control	Optional	Optional	Optional	YES	YES	YES	YES	YES	YES	YES
Constant Run fan	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
Burn Rate kgs / hr	45	48	15	45	150	50	300	55-70	65-100	65-100